

WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY



BETON TROWEL n.v.

Tel. +32 (0)52 315 350
 Tel. +32 (0)52 315 351
 Fax +32 (0)52 315 359
 info@betontrowel.com

www.betontrowel.com
 Nijverheidsstraat 10
 BE-1840 Londerzeel - Belgium

**ROTOPOKA
 VIBRATOR**



ROTOPOKA INTERNAL PENDULUM FLEXIBLE DRIVE VIBRATOR

Model	Head Diam	Length	Hz	Frequency	Amplitude	Shaft	Shaft Diam	Coupling
BTRP25	25mm	389mm	260	15600	0.72mm	6m	24mm	Twin claw
BTRP35	35mm	370mm	220	13200	0.82mm	6m	30mm	Twin claw
BTRP50	50mm	451mm	200	12000	1.15mm	6m	36mm	Twin claw
BTRP60	60mm	406mm	200	12000	1.20mm	6m	36mm	Twin claw
BTRP35	35mm	370mm	220	13200	0.82mm	12m	30mm	Twin claw
BTRP50	50mm	451mm	200	12000	1.15mm	12m	36mm	Twin claw
BTRP60	60mm	406mm	200	12000	1.20mm	12m	36mm	Twin claw



- SQUARE FRAME PROTECTS ENGINE PLUS AV MOUNTS ON ENGINE DECK PROTECT THE MOTOR
- QUICK ENGAGE/RELEASE TWIN CLAW COUPLING
- SHAFT DRIVE COUPLING INTERCHANGEABLE WITH DYNAPAC/WACKER/GCM/BELLE POWER UNITS
- FLEXSHAFT HAS ARMoured SPIRALS BOTH ENDS TO PROTECT THE SHAFT
- POWER OPTIONS : HONDA GX160 5.5hp, ROBIN EY20, YANMAR DIESEL L48 4.7hp, ELECTRIC 230V & 110V , BTP200 6.5hp